

2014 Superior Broom DT80CT



SB Manufacturing, Inc.
3707 West McCormick
Wichita, KS 67213
888-341-8707
www.superiorbroom.com

The Superior Broom has many features not found on any other Side Cast Sweepers, including low noise level in the cab, rear leaf spring suspension, and touch pad control panel for the remote mounted integrated hydraulic manifold that keeps the hydraulic heat and noise outside of the cab.

GENERAL INFORMATION

M.S.R.P. Request a Quote

BODY

Power Steering Orbital, hydraulic

Suspension Spring

ENGINE & DRIVETRAIN

Engine Make Cummins

Engine Model B3.3T

Engine Type 199 ci

Horsepower 74 hp

Fuel Type Diesel

Fuel Tank Capacity 41 gal.

Transmission Infinitely variable hydrostatic pump and motor driving a differential rear axle through a 2-speed gearbox

Travel Speed Low Range: 0-12 mph
High Range: 0-34 mph

HYDRAULICS

Hydraulic System Load compensated pump
28 gpm with 3,000 PSI operating pressure
10 micron high pressure suction filter

OPERATIONAL

Sweeping Path 96 in.

Number of Rear Axles (1) heavy-duty semi-float differential

Wheels (4) 15 x 6 in., 6-bolt, steel spoke

Tires (4) 57235/75R15, radial, load range C

DIMENSIONS

Length 172 in.

Height 103 in. (with canopy)

Width 98 in. (transport)

Weight 5,300 lbs. (with canopy)

Wheelbase 133 in.

Turning Radius 13 ft. (inside)

Customer Date Price \$

Salesperson Signature _____

Comments

Legal Notice: Manufacturer Name, Logo and Model Information are Registered Trademarks of the Manufacturer. Specifications and other information are subject to change without notice. No representation of accuracy is made. Image is believed to be in the public domain or used with permission.